

DT 275 PRO

High-isolation on-ear monitoring headphones

Order # 1002666



FEATURES

- Compact on-ear design and rotating ear cups
- High passive isolation and balanced sound tuning
- Flexible in any setup with lockable cable connection on the left and right ear cup
- High wearing comfort due to light weight and soft ear pads
- Durable and service-friendly thanks to replaceable components



beyerdynamic

DT 275 PRO

High-isolation on-ear monitoring headphones

Order # 1002666

DESCRIPTION

The DT 275 PRO is a closed-back monitoring headphone with a high passive isolation. It is ideal for use in noisy environments.

The balanced sound tuning ensures clear speech and signal assessment.

The detachable, single-sided cable features a locking mechanism and can be connected to either the right or left ear cup. The decoupled cable design reduces cable and handling noise while supporting clean, flexible workflows with the camera, recorder, interface, mixing console or DJ mixer.

Due to its compact on-ear design and swivelling ear cups, the DT 275 PRO is easy to store and is quickly ready for use again.

The DT 275 PRO stands out due to its light weight and soft, sweat-resistant leatherette ear pads. If required, the ear pads, headband pad and cable can be easily replaced.

SUPPLIED ACCESSORIES / REPLACEMENT PARTS

- DT 275 PRO headband pad, black Order # 1003244
- DT 275 PRO / EDT 275 PRO ear pads Order # 1003234
- DJ 300 PRO X / CLUB / DT 275 PRO connecting cable Order # 1002589
- Mini jack (3.5 mm) to 1/4" (6.35 mm) jack adapter Order # 1002678

TECHNICAL SPECIFICATIONS

Transducer	Dynamic
Acoustic design	Closed-back
Wearing type	On-ear
Frequency response	5 - 24,000 Hz
Nominal impedance	45 Ω
Sound pressure level @ 1mW / 500 Hz	105 dB SPL
Sound pressure level @ 1V / 500 Hz	119 dB SPL
T.H.D.	< 0.04 %
Maximum short-term power handling capacity	100 mW
Ambient noise attenuation	22 dBA
Nominal headband pressure	4.3 N
Weight (without connecting cable)	195 g
Length and type of cable	1.5 m / special cable (coiled and straight)
Connection	Gold-plated mini stereo jack plug (3.5 mm) and 1/4" adapter (6.35 mm)

(all specifications acc. to EN 60 268-7)



beyerdynamic