

# AX-48 PRO ACCESSORIES

## AX-48 Pro Mic Boom

- Microphone Boom and Adapter (AX-48 ProMic, #17366)



## AX-48 Pro Third Tier

- Super Clamp (CMP-485, #11853)
- 13" Tribar Pair Arms (TBR-130, #16535)
- 18" Tribar Pair Arms (TBR-180, #16534)



## AX-48 Pro Mic Tote Bag

- Heavy-duty Tote Bag (AX-48 ProBag, #17367)



Visit **[ultimatesupport.com](http://ultimatesupport.com)**  
to read full warranty details  
& to **register for warranty**.



### ULTIMATE SUPPORT LIMITED LIFETIME WARRANTY

Ultimate Support products are constructed of the finest materials and designed and tested to stand up to the demanding lifestyle of the touring musician, gigging DJ, and working sound engineer. In the unlikely event that a product should fail due to manufacturing defect, Ultimate Support is pleased to repair or replace that product.

Please see **[www.ultimatesupport.com](http://www.ultimatesupport.com)** for more information.

This warranty applies to the original purchaser only and does not include damage to the product resulting from normal wear and tear, accident, misuse, improper installation or operation, or unauthorized repair or alterations.

800.525.5628 . [www.ultimatesupport.com](http://www.ultimatesupport.com)

Copyright 2015, Ultimate Support Systems . All Rights Reserved

## ULTIMATE SUPPORT® THE STRENGTH OF INNOVATION™

# USER MANUAL

## AX-48 PRO ACCESSORIES MIC BOOM & ADAPTER

AX-48 Pro Mic Boom/17366



Rev. 1 • 05.15.15 • UM-KEY-AX-48ProMIC

### ULTIMATE SUPPORT® LIMITED LIFETIME WARRANTY

# SETUP

## PARTS INCLUDED:

- A. Ulti-Boom Pro (mic boom)
- B. AX-48TA (adapter)
- C. (2) Bolts
- D. Allen Wrench



**STEP 1:** Locate grooves on APEX® AX-48 Pro top plate.



**STEP 2:** Using a flat tip screw driver, remove accessory cap by wedging head into grooves and gently applying pressure.



**STEP 3:** Remove accessory cap.



**STEP 4:** Replace accessory cap with AX-48TA adapter.



**STEP 5:** Using provided allen wrench, screw bolts into place. Do not over tighten.



**STEP 6:** Attach Ulti-Boom Pro to the top of the accessory cap and adjust as desired.