ULTIMATE

THE STRENGTH OF INNOVATION

THE MOST ADVANCED

FEATURING TELELOCK®

SPEAKER STAND TS-90B

The TeleLock portable speaker stand allows one person to easily and safely raise and lower heavy speakers.









FEATURES OF TS-90B

Patented TeleLock® - TeleLock allows one person to easily and safely raise and lower heavy speakers.

Heavy-Duty Stand - Larger diameter tubing and metal reinforced clamps securely support more weight than other stands.

Truly Portable - Quickly folds into a compact, lightweight unit. Tote bags available: BAG-90 and BAG-90D.

Limited Lifetime Warranty - Constructed of the finest materials and backed by our awardwinning customer support. For full details, exclusions and limitations as well as information on obtaining warranty service, visit **www.ultimatesupport.com**.

INSTRUCTIONS FOR SETTING UP THE STAND

- 1. Put the TELELOCK COLLAR into the "RAISE" position, Raise center tube 6" 10".
- Put speaker on stand and raise telescoping tube to desired height. In the "RAISE" position the TELELOCK COLLAR keeps the telescoping tube from sliding back down. Set to "LOCK" position.
- 3. To lower speaker, SLOWLY rotate ARROW on TeleLock collar to "LOWER" position until speaker starts to lower. To slow descent, turn collar toward the "RAISE" position. Use caution. 4. When removing the speaker, rotate ARROW to the "LOCKED" position.

NOTE: Instructions for tripod base & socket adapter are available on website.

Visit www.ultimatesupport.com to download a detailed product manual, read full warranty details and to register your warranty.

TS-90B

- Item #13908 black
- Height 3'8" 6'7" (1118 mm - 2007 mm)
- Weight 6.2 lbs. (2.8 kg)
- Base diameter 47" (1194 mm)

- Load capacity of 150 lbs. (68.2 kg)
- Folded 43.5" x 5.5"
 (1105 mm x 140 mm)
- Fits 1-1/2" (38 mm),
 1-3/8" (35 mm) speaker sockets